

# INDUSTRIAL TUMBLER DRYER

TX  
RANGE

TX9

9 KG  
20LB



## FEATURES

- Standard stainless steel drum
- Anthracite grey skin plate
- Inox top panel
- Easy-to-use microprocessor (ECT)
- Axial airflow
- 210° door opening for easy loading and unloading
- Intuitive control with simple selection and 3 programs

## OPTIONS

- Stainless steel front
- Reverse drum
- Residual moisture control Sensodry®:
  - safe drying of delicate linen
  - humidity detection in %
- Heating power from 6 (kW) up to 12 (kW), to match various installation requirements
- Coin operated version




23% MORE  
DRYING  
EFFICIENT\*



20% LOWER  
ENERGY  
CONSUMPTION\*



30%  
FASTER  
EVAPORATION\*



\*vs previous generation, Duration of total dry cycle time from (55±1)% initial humidity to (8+1 -0)% with no cool down time. Test performed in our lab according to ISO9398-2:2003 standard for 100% cotton towels, with 12Kw.

TYPE		TX9
<b>CAPACITY</b>		
Capacity 1:18	kg (lb)	11(24)
Capacity 1:22	kg (lb)	9(20)
Drum volume	l	195
Drum diameter	mm	Ø 670
Drum depth	mm	555
<b>DOOR</b>		
Door opening	mm	Ø 500
Opening direction		Right (reversible)
Door opening angle		210°
<b>DRYING PERFORMANCE</b>		
Airflow type		Axial
Airflow	m <sup>3</sup> /h	300
<b>HEATING</b>		
Heating type		Electric
Heating power	kW	6 / 9 / 12
Total power supply	kW	6,4 / 9,4 / 12,4
Electrical connection		3x220-230V 50Hz 3x220-230V 60Hz 3x240V 50Hz 3x380-415V+N 50Hz 3x380-415V+N 60Hz 3x380-415V 50Hz 3x380-415V 60Hz 3x440V 60Hz
<b>MOTOR</b>		
Fan	kW	0,25
Drive	kW	0,25
<b>CONNECTION</b>		
Exhaust	mm	150
<b>PROGRAMMER</b>		
		Easy Control
<b>NOISE</b>		
Drying sequence	db	55
<b>DIMENSIONS</b>		
H×W×D	mm	1150x710x945
Net weight	kg	125
<b>TRANSPORT DATA</b>		
Packed H×W×D	mm	1253x752x970
Gross weight	kg	180

